

## Wide Base Scissor

Blue Giant Wide Base Series Scissor Lift Tables are cost-effective and ergonomically designed to meet all your application requirements. The wide base provides enhanced stability and support to handle larger loads of up to 6,000 lb (2,721 kg).

### FEATURES

- Heavy-duty cylinders
- Heavy-duty steel legs
- Internal power units
- Lifetime lubricated bearings
- Safety hinged maintenance blocks
- Standard hand controls

### OPTIONS

- Accordion skirts
- Conveyor
- External power unit
- Electric toe guards
- Foot pedal control
- High cycle
- Oversized platform
- PLC controlled
- Platform with beveled edges
- Portability package
- Tilt table mounted to lift
- Travel limit switch
- Turn table mounted to lift



## SPECIFICATIONS

Model Number	Load Capacity	Lowered Height	Raised Height	Standard Platform	Maximum Platform	Standard Motor	Weight
<b>LFTWB24 SERIES – 24" TRAVEL</b>							
LFTWB24-20	2,000 lb (907 kg)	7.5" (191 mm)	31.5" (800 mm)	36" x 36" (914 x 914 mm)	60" x 60" (1,524 x 1524 mm)	1 HP	720 lb (327 kg)
LFTWB24-40	4,000 lb (1,814 kg)						740 lb (336 kg)
LFTWB24-60	6,000 lb (2,721 kg)					2 HP*	790 lb (358 kg)
<b>LFTWB36 SERIES – 36" TRAVEL</b>							
LFTWB36-20	2,000 lb (907 kg)	7.5" (191 mm)	43.5" (1,105 mm)	36" x 48" (914 x 1,219 mm)	60" x 72" (1,524 x 1,829 mm)	1 HP	860 lb (390 kg)
LFTWB36-40	4,000 lb (1,814 kg)						900 lb (408 kg)
LFTWB36-60	6,000 lb (2,721 kg)					2 HP*	960 lb (435 kg)
<b>LFTWB48 SERIES – 48" TRAVEL</b>							
LFTWB48-20	2,000 lb (907 kg)	7.5" (191 mm)	55.5" (1,410 mm)	36" x 64" (914 x 1,626 mm)	60" x 96" (1,524 x 2,438 mm)	1 HP	1,020 lb (463 kg)
LFTWB48-40	4,000 lb (1,814 kg)						1,070 lb (485 kg)
LFTWB48-60	6,000 lb (2,721 kg)					2 HP*	1,120 lb (508 kg)
<b>LFTXB36 SERIES – 36" TRAVEL</b>							
LFTXB36-20	2,000 lb (907 kg)	7.5" (191 mm)	43.5" (1,105 mm)	48" x 48" (1,219 x 1,219 mm)	72" x 72" (1,829 x 1,829 mm)	1 HP	950 lb (431 kg)
LFTXB36-40	4,000 lb (1,814 kg)						990 lb (449 kg)
LFTXB36-60	6,000 lb (2,721 kg)					2 HP*	1,050 lb (476 kg)
<b>LFTXB48 SERIES – 48" TRAVEL</b>							
LFTXB48-20	2,000 lb (907 kg)	7.5" (191 mm)	55.5" (1,410 mm)	48" x 64" (1,219 x 1,626 mm)	72" x 96" (1,829 x 2,438 mm)	1 HP	1,110 lb (503 kg)
LFTXB48-40	4,000 lb (1,814 kg)						1,160 lb (526 kg)
LFTXB48-60	6,000 lb (2,721 kg)					2 HP*	1,250 lb (567 kg)
<b>LFTXB60 SERIES – 60" TRAVEL</b>							
LFTXB60-20	2,000 lb (907 kg)	10" (254 mm)	70" (1,778 mm)	56" x 88" (1,422 x 2,235 mm)	84" x 120" (2,134 mm x 3,048 mm)	1 HP	1,650 lb (748 kg)
LFTXB60-40	4,000 lb (1,814 kg)						1,725 lb (782 kg)
LFTXB60-60	6,000 lb (2,721 kg)					2 HP*	1,800 lb (816 kg)

## CUSTOM DESIGNS

Engineering and design services are available for unique applications.